

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Bambù

Code : 1048601A

PRODUCT FAMILY

- Outdoor residential round shaped complete with base for plinth/floor installation (IP55)

MATERIAL CHARACTERISTICS

- Housing in aluminium plated steel and integrated base in hot galvanised steel, and painted (metallic grey RAL 9006 and black textured)
- Body and integrated base in stainless steel AISI 316L
- Diffuser, flush with body in translucent UV resistant, internally prismatic PC (polycarbonate), attached to the body through a bayonet connector and sealed with a silicone gasket
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- Metallic grey RAL 9006
- Black textured

LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS

- Luminaire designed for max 21W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø50x190mm

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire installed directly to plinth/floor with n.3 screws (not supplied) and sealed with a gasket
- Tool-free extractable gear tray from the top
- Cable clamp on gear tray, Ø5-12mm
- Terminal for cables Ø2.5mmq
- Ordinary maintenance carried out by removing diffuser by rotating and lifting, possible through bayonet connector
- The "T"-3 ways IP68 connector cannot be placed inside the luminaire

DIMENSIONS

- Ø76x660mm
- Ø76x950mm
- Ø76x1640mm
- Round shaped base Ø116

OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:


- IP68 connector - COD.CS093000
- "T"-3 ways IP68 connector - COD.CS093001

- Warranty: 5 years

Rev 02-28/04/2016

Details

- Conformity with CEE directives
- CLASS I
- IK05
- CLASS A+
- CLASS A
- IP 55



220-240V 50/60Hz 21W max E27

