

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Sfera Acrylic Reflex 1010 - IP44

Code : 1010201T

#### PRODUCT FAMILY

- Globe-shaped luminaire complete with base (IP44) for use with poles or brackets Ø60mm on top, for uplight installation

#### MATERIAL CHARACTERISTICS

- Spherical diffuser in PMMA (acrylic) half painted internally with reflective aluminium and externally with opaque black paint
- Diameter Ø250mm, Ø300mm, Ø400mm, with bayonet neck
- Base made of self extinguishing V2 PC (polycarbonate)
- A2 stainless steel screws

#### COLOUR

- Transparent/Black

#### LIGHTING CHARACTERISTICS

- Light source in fixed position
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- Luminaire designed for max 20W LED lamp, E27 lamp holder, supply tension max 250V (Ø250mm)
- Luminaire designed for max 21W LED lamp, E27 lamp holder, supply tension max 250V (Ø300mm)
- Luminaire designed for max 27W LED lamp, E27 lamp holder, supply tension max 250V (Ø400mm)
- Max lamp dimension allowed Ø65xL110mm (Ø250mm)
- Max lamp dimension allowed Ø80xL190mm (Ø300mm)
- Max lamp dimension allowed Ø80xL190mm (Ø400mm)

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS


- Luminaire for use with poles or brackets Ø60mm on top, to be mounted through a screw (included)
- Self-adjusting cord block for cable max Ø10mm
- Ordinary maintenance can be conducted by removing the diffuser

- Warranty: 5 years

Rev 03 -20/02/2023

#### Details

- Conformity with EU Directives
- Double insulation/class II
- IK08
- IP 44



230V 50Hz 20W max E27			
CE		IK08	IP44

