

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Wired base Sfera Ø600 - IP65

Code : 2000901N

PRODUCT FAMILY

- Wired base, for spherical diffuser Ø600mm, suitable for uplight installation on poles or brackets Ø60mm on top (IP65)

MATERIAL CHARACTERISTICS

- Base in thermo-setting resin, characterised by its strength and flame resistance
 - Cone covering gear tray in PC (polycarbonate) and painted with bi-component aluminium metallic acrylic enamel, formulated in order to create a pleasing and protective finish whilst achieving good mechanical and chemical strength
 - Silicone gaskets
 - A2 stainless steel screws

COLOUR

- Black

LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
 - Round symmetrical light throw

WIRING CHARACTERISTICS

- Easily extractable gear tray made from galvanised steel for extraordinary maintenance
 - Luminaire designed for max 33W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
 - Max lamp dimension allowed Ø100xL210mm

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Wired base for use with poles or brackets Ø60mm on top, fixed with n.3 screws
 - Ordinary maintenance by turning the diffuser with bayonet neck
 - Cable clamp on gear tray, Ø15mm max

OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:

- Quasar Ø600 - COD.1469300A
 - Giubar Ø600 - COD.1472400A

RECOMMENDED POLES TO BE ORDERED SEPARATELY:


- Toce H3000 - System A - COD.1410100N
 - Toce H3000 - System B - COD.1411100N
 - Piave H4200 - System A - COD.1407100N
 - Piave H5200 - System A - COD.1407200N
 - Piave H4200 - System B - COD.1427100N
 - Piave H5200 - System B - COD.1427200N
 - Brembo H4000 - System A - COD.1405100N
 - Brembo H4000 - System B - COD.1425100N
 - Don H4700 - System A - COD.1412100S
 - Don H5800 - System A - COD.1412200S
 - Don H4200 - System B - COD.1422100S
 - Don H5200 - System B - COD.1422200S
 - Varano wall fixing uplight/downlight installation - COD.1000110N
 - Varano uplight/downlight installation H4000 - System A 1 light - COD.1140100N
 - Varano uplight/downlight installation H4000 - System A 2 lights - COD.1140200N
 - Varano uplight/downlight installation H4000 - System A 3 lights - COD.1140300N
 - Varano uplight/downlight installation H5000 - System A 1 light - COD.1141100N
 - Varano uplight/downlight installation H5000 - System A 2 lights - COD.1141200N
 - Varano uplight/downlight installation H5000 - System A 3 lights - COD.1141300N
 - Varano uplight/downlight installation H4000 - System B 1 light - COD.1145100N
 - Varano uplight/downlight installation H4000 - System B 2 lights - COD.1145200N
 - Varano uplight/downlight installation H4000 - System B 3 lights - COD.1145300N


• Warranty: 2 years

Rev 02-14/11/2019

Details

- Conformity with CEE directives
- Double insulation/class II
- IK06
- IP 65



220-240V 50/60Hz 33W max E27			
CE		IK06	IP65