
47032 bertinoro (FC) Italia
via s.croce, 121 (z.i.)
tel. +39 0543 4687
fax +39 0543 449051
info@marecoluce.it
www.marecoluce.it

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Toce Ø60

Code : 1410100N



PRODUCT FAMILY
- Cilyndrical Ø60mm pole for ground or plinth/floor fixing, suitable for luminaire installation on top

MATERIAL CHARACTERISTICS
- Cylindrical pole conforming to DIN norm, made of hot-dip galvanised steel 75m UNI EN 1461 and painting
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection
against weathering
- A2 stainless steel screws

BURIED POLE - SYSTEM A
- Cylindrical pole Ø60x3000mm conforming to DIN norm, for ground fixing made of hot-dip galvanised
steel 75m UNI EN 1461
- Total ground height 2500mm
- Suggested plinth 600x600x700mm

FLANGED POLE - SYSTEM B
- Cylindrical pole Ø60x3000mm conforming to DIN norm, for plinth/floor fixing complete with flange made of
hot-dip galvanised steel 75m UNI EN 1461
- Total ground height 3000mm
- 200x200mm flange, 8mm thick made of hot-dip galvanised steel 75m UNI EN 1461
- Suggested plinth 600x600x700mm

COMPULSORY ACCESSORY SYSTEM B - COD.40000001
- Counter flange 200x200x3mm and anchor bolts kit M14x330mm (n°4) with n°8 nut and n°8 washers made of
hot-dip galvanised steel 75m UNI EN 1461

COLOUR
- Anthracite RAL 7016 textured

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS
- Hole for cable passage (buried part of pole System A)
- Hole on flange for cable passage into pole and hole on pole for earthing cable (System B)
- M8 earthing bolt

Rev. 3 - 09/03/2022

Details
• IP

