

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Eos 360

### Code : 1038101S

#### PRODUCT FAMILY

- Outdoor residential triangular shaped complete with base for plinth/floor installation (IP65)

#### MATERIAL CHARACTERISTICS

- Painted reinforced thermoplastic base and top cover in NY-FV30%
- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Diffuser, flush with body, in transparent PMMA (acrylic), internally prismatic
- Silicone gaskets
- A2 stainless steel screws

#### COLOUR

- Anthracite RAL 7016 textured
- Metallic grey RAL 9006

#### LIGHTING CHARACTERISTICS

- Light source in fixed position
- Front light throw

#### WIRING CHARACTERISTICS

- Luminaire designed for max 21W LED lamp, E27 lamp holder, supply tension max 250V
- Max lamp dimension allowed Ø60xL170mm
- External cable and IP68 terminal block supplied (housed inside fitting)
- Use only a flexible supply cable in double sheath type HAR, with external diameter between Ø7 and Ø12mm, and section of the internal conductors between 0.5 and 1.5mmq

#### INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire installed directly to plinth/floor with n.3 screws (not supplied)
- Ordinary maintenance carried out by loosening the closing screws in top cover

#### DIMENSIONS


- 130x450mm
- Triangular base 190mm

- Warranty: 2 years

Rev 03-29/10/2019

#### Details

- Conformity with EU Directives
- Double insulation/class II
- IK06
- IP 65



20W max E27

CE

IK

06

IP65

