

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Varano wall fixing uplight/downlight

**Code : 1000110S**

#### PRODUCT FAMILY

- Wall system for mounting uplight and downlight
- Suitable for globes with base IP44 only for upright mounting, and for globes with base IP65 Ø400/500mm for upright and downlight mounting

#### MATERIAL CHARACTERISTICS

- Ø40mm tubular arm, with 180° curve, a total height of 700mm, and an outreach of 430mm in hot-dipped galvanised steel 75m UNI EN 1461 complete with upper closing cap and painting
- Connector for wall/bracket made in galvanised steel 75m UNI EN 1461 and painting
- Connector (Ø60mm) at end of bracket in black moulded in NY/FV30% suitable for globes with base IP44 range 1080 or for globes with base IP65 Ø400/500mm (range 2000)
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

#### WIRING CHARACTERISTICS

- Predisposed holes for supply cables and earthing cable

#### COLOUR

- Anthracite RAL 7016 textured

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Fixing of wall/arm bracket through 2 expansion caps (not supplied)

#### DIMENSIONS

- 700x430mm

Rev. 3 - 10/03/2022

#### Details

- IP

