

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Carezza wall fixing uplight

Code : 1000200N

PRODUCT FAMILY

- Wall system for mounting uplight, suitable for globes with base IP44 range 1080 Ø250/300mm

MATERIAL CHARACTERISTICS

- Ø28mm tubular arm, with 180° curve, a total height of 610mm, and an outreach of 259mm in hot-dipped galvanised steel 75µm UNI EN 1461 and painting complete with upper closing cap
- Connector for wall/bracket in hot-dipped galvanised steel 75µm UNI EN 1461 and painting
- Connector/cover Ø60mm at end of bracket in black moulded NY/FV30% (suitable for globes with base IP44 range 1080)
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

WIRING CHARACTERISTICS

- Predisposed holes for supply cables and earthing cable

COLOUR

- Anthracite RAL 7016 textured

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Fixing of wall/arm bracket through 2 expansion caps (not supplied)

DIMENSIONS

- 610x259mm

Rev. 3 - 10/03/2022

Details

- IP

