

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Lira 40 Directional

Code : 4044484W

PRODUCT FAMILY

- IP67 inground LED marker light for effect lighting Ø40mm, requiring recessed box for floor mounting, or retaining springs for false ceiling mounting

MATERIAL CHARACTERISTICS

- Housing in stainless steel AISI 316L
- AISI 316L stainless steel casting upper ring 1,2 or 4 ways and polished finish
- Flat, transparent, tempered glass diffuser, 6mm thick
- PMMA (acrylic) lens with high transmittance
- Max load 500Kg at 20Km/h
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- Stainless steel

LIGHTING CHARACTERISTICS

- LED's lighting source in fixed position
- Immediately ON at 100% of light flux
- Monochromatic LED module (1 Led)

WIRING CHARACTERISTICS

- Metal PG9 cable gland
- Remote electronic driver compulsory
- Pre-wired with H05RN-F 2x0.5mmq cable (40cm) for the connection to the mains
- IPSC included: Protected against reversal of polarity, overvoltage and short circuit

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Inground uplight for use with recessed box accessory (to be ordered separately)
- Ceiling downlight for direct mounting, requiring Ø32mm hole with locking mechanism (supplied separately)
- Ordinary and extraordinary maintenance not necessary
- Drivers CS160017 or CS160024 cannot be placed inside the recessed box
- The "T"-3 ways and linear IP68 connector cannot be placed inside the recessed box

COMPULSORY ACCESSORY FOR PAVEMENT MOUNTING TO BE ORDERED SEPARATELY:

- Circular recessed box Ø100x80mm - COD.70000003
- Tubular recessed box Ø35x70mm - COD.70000007

COMPULSORY ACCESSORY FOR FALSE CEILING MOUNTING TO BE ORDERED SEPARATELY:

- False ceiling locking mechanism - COD.4000001W

DIMENSIONS

- Ø40x66mm

TECHNICAL SPECS

- Step MacAdam: 4
- Lifetime Led's: L80/B50 - 40Kh Tc 70°C
- Warranty: 5 years

TECHNICAL SPECS 4000K - 350mA - 1W

- Flusso scheda LED: 124lm@tc25°C
- Luminaire output 1 way: 8lm@ta25°C
- Luminaire output 2 ways: 3lm@ta25°C
- Luminaire output 4 ways: 6lm@ta25°C

TECHNICAL SPECS 4000K - 500mA - 2W

- Flusso scheda LED: 167lm@tc25°C
- Luminaire output 1 way: 11lm@ta25°C
- Luminaire output 2 ways: 4lm@ta25°C
- Luminaire output 4 ways: 8lm@ta25°C

TECHNICAL SPECS 4000K - 700mA - 3W

- Flusso scheda LED: 217lm@tc25°C
- Luminaire output 1 way: 15lm@ta25°C
- Luminaire output 2 ways: 6lm@ta25°C
- Luminaire output 4 ways: 10lm@ta25°C

TECHNICAL SPECS 3000K - 350mA - 1W

- Flusso scheda LED: 109lm@tc25°C
- Luminaire output 1 way: 7lm@ta25°C
- Luminaire output 2 ways: 3lm@ta25°C
- Luminaire output 4 ways: 5lm@ta25°C

TECHNICAL SPECS 3000K - 500mA - 2W

- Flusso scheda LED: 147lm@tc25°C
- Luminaire output 1 way: 10lm@ta25°C
- Luminaire output 2 ways: 4lm@ta25°C
- Luminaire output 4 ways: 7lm@ta25°C

TECHNICAL SPECS 3000K - 700mA - 3W


- Flusso scheda LED: 191lm@tc25°C
- Luminaire output 1 way: 13lm@ta25°C
- Luminaire output 2 ways: 5lm@ta25°C
- Luminaire output 4 ways: 9lm@ta25°C

Rev. 4 - 20/11/19

Details

- Conformity with EU Directives
- Class III
- IK08
- RG1
- RG2
- CRI>80
- IP 67





350/500/ 700mA 1/2/3W					
CE		IK08	RG	RG	CRI ≥80 IP67

