

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Lira 150

Code : 4152891W

PRODUCT FAMILY

IP67 Inground/ wall LED Marker light for effect lighting. Drive-over (2000kg max. at 20km/h), requiring recessed box

MATERIAL CHARACTERISTICS

Body in anodised, die-cast aluminium alloy EN AB 46100

Directional ring in anodised aluminium – available with 1, 2 and 4 light beams

Diffuser in transparent, tempered glass

Colour: Aluminium

Gaskets in silicone

Screws in stainless steel A2

LIGHTING CHARACTERISTICS

- Vossloh-Schwabe LED Module - Direct supply tension LED versions

LED Output

8W - 4000K 688 lm

8W - 3000K 656 lm

LED luminaire output

8W - 4000K 384 lm

8W - 3000K 366 lm

Step MacAdam 3

Cable included 3x1mmq H05RNF (0.4mt)

- Version GU10 lamp holder

Adjustable optics $\pm 15^\circ$

Direct supply tension 220-240V 50/60Hz

Cable included 3x1mmq H05RNF (0.4mt)

WIRING CHARACTERISTICS

Factory-sealed termination chamber – utilising resin to guarantee sealing

Metal PG9 cable gland

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Inground/wall marker light for use with recessed box accessory (supplied separately)

Ordinary maintenance (usually unnecessary for LED products) by removing the n.4 screws from ring and removing diffuser

MEASUREMENT CHARACTERISTICS

Ring $\varnothing 150\text{mm}$ (with 28mm height)

Depth 148mm

Maximum drive-over load: 2000Kg at 20Km/h

ACCESSORIES

Compulsory:

Recessed box (code: 7000.0005)

Optional:

IP68 connector (code: CS093000)

'T'- 3 way IP68 connector (code: CS093001)

Rev 03 - 24/07/2018


Details

- Conformity with CEE directives

- Class III

- IP 67



198-264V 50/60Hz 8W		
CE		IP67