

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Lira 180

Code : 4180784W

PRODUCT FAMILY

IP67 Inground LED Uplight. Drive-over (2500kg max. at 20km/h) with recessed box and factory-sealed termination chamber

MATERIAL CHARACTERISTICS

Body in anodised, die-cast aluminium alloy EN AB 46100
 Ring in S.Steel AISI 316L with 4mm thickness and micro-shot blasted
 Diffuser in flat, tempered glass, and with a thickness of 12mm
 Gear tray in S.Steel AISI 304L
 Colour: S.Steel

Gaskets in silicone
 Screws in stainless steel A2

LIGHTING CHARACTERISTICS

•Citizen LED Module with inner driver (mains powered 220-240V 50/60Hz)

LED Output

6.8W - 4000K 834 lm
 6.8W - 3000K 809 lm

LED luminaire output

6.8W - 4000K 336 lm
 6.8W - 3000K 326 lm

Adjustable optic $\pm 15^\circ$

Darkoo lens with beam angle 8°

Step MacAdam 3

Cable included 3x1.5mmq H05RN-F (1mt)

•Vossloh-Schwabe LED Module - 220-240V 50/60Hz Direct supply tension

LED Output

15W - 4000K 1425 lm
 15W - 3000k 1360 lm

LED luminaire output

15W - 4000K 574 lm
 15W - 3000k 548 lm

Adjustable optic $\pm 15^\circ$

beam angle

14°

32°

Step MacAdam 3

Cable included 3x1.5mmq H05RN-F (1mt)

WIRING CHARACTERISTICS

metric cable gland

Factory-sealed termination chamber – utilising resin to guarantee sealing

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Inground Uplight for use with recessed box accessory (supplied separately)

Ordinary maintenance (usually unnecessary for LED products) by removing the n.4 screws from ring and removing diffuser

MEASUREMENT CHARACTERISTICS

Ring $\varnothing 180\text{mm}$ (with 4mm overhang)

Depth 205.7mm

Maximum drive-over load: 2500Kg at 20Km/h

ACCESSORIES

Compulsory:

Recessed box (code: 7000.0002)

Optional:

IP68 connector (code: CS093000)

T'- 3 way IP68 connector (code: CS093001)

Rev 04-24/07/2018

- Conformity with CEE directives
- IP 67



220-240V 50/60Hz 6,8W	
CE	IP67