

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Lira 240

**Code : 4240784W**

#### PRODUCT FAMILY

IP67 Inground LED Uplight. Drive-over (2500kg max. at 20km/h) with factory-sealed termination chamber and requiring recessed box

#### MATERIAL CHARACTERISTICS

Body in anodised, die-cast aluminium alloy EN AB 46100

Ring in S.Steel AISI 316L Ø240 with 4mm thickness and micro-shot blasted

Diffuser in flat, tempered glass, and with a thickness of 12mm

Colour: S.Steel

Gaskets in silicone

Screws in stainless steel A2

#### LIGHTING CHARACTERISTICS

•Citizen LED Module with inner driver (mains powered 220-240V 50/60Hz)

##### LED Output

6.8W - 4000K 834 lm

6.8W - 3000K 809 lm

##### LED luminaire output

6.8W - 4000K 675 lm

6.8W - 3000K 655 lm

Adjustable optic ±15°

Darkoo lens with beam angle 8°

Step MacAdam 3

Cable included 3x1.5mmq H05RN-F (1mt)

•Vossloh-Schwabe LED Module - 220-240V 50/60Hz Direct supply tension

##### LED Output

20W - 4000K 1900 lm

20W - 3000k 1800 lm

##### LED luminaire output

20W - 4000K 1466 lm

20W - 3000k 1429 lm

Adjustable optic ±15°

beam angle

14°

32°

Step MacAdam 3

Cable included 3x1.5mmq H05RN-F (1mt)

#### WIRING CHARACTERISTICS

metric cable gland

Factory-sealed termination chamber – utilising resin to guarantee sealing

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Inground Uplight for use with recessed box accessory (supplied separately)

Ordinary maintenance (usually unnecessary for LED products) by removing the n.4 screws from ring and removing diffuser

#### MEASUREMENT CHARACTERISTICS

Ring Ø240mm (with 4mm height)

Depth 208mm

Maximum drive-over load: 2500Kg at 20Km/h

#### ACCESSORIES

Compulsory:

Recessed box (code: 7000.0006)

Optional:

IP68 connector (code: CS093000)

T'- 3 way IP68 connector (code: CS093001)

Rev 04-24/07/2018

#### Details

• Conformity with CEE directives

• IP 67



6,8W	
CE	IP67