

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Deva system

Code : 3016210M

PRODUCT FAMILY

- Pole with brackets for 1,2 or 3 lights version, for ground or plinth/floor fixing only for Deva Led luminaire

MATERIAL CHARACTERISTICS

- Cylindrical pole conforming to DIN norm, made of hot-dip galvanised steel 75m UNI EN 1461 and painting
- Deva Led fixing swivel joint allowing inclination/rotation in die cast aluminium anodized and painted
- Ø30mm pipe connecting Deva Led to the pole adapter, in hot-dipped galvanized steel 75m UNI EN 1461 then painted
- Ø60mm pole adapter in die cast aluminium anodized and painted
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

BURIED POLE - SYSTEM A

- Cylindrical pole Ø60/30x2600/3600mm conforming to DIN norm, for ground fixing made of hot-dip galvanised steel 75m UNI EN 1461
- Total ground height 2100/3100mm
- Suggested plinth 600x600x700mm

FLANGED POLE - SYSTEM B

- Cylindrical pole Ø60/30x2600/3600mm conforming to DIN norm, for plinth/floor fixing complete with flange made of hot-dip galvanised steel 75m UNI EN 1461
- Total ground height 2100/3600mm
- 200x200mm flange, 8mm thick made of hot-dip galvanised steel 75m UNI EN 1461
- Suggested plinth 600x600x700mm

COMPULSORY ACCESSORY SYSTEM B - COD.40000001

- Counter flange 200x200x3mm and anchor bolts kit M14x330mm (n°4) with n°8 nut and n°8 washers made of hot-dip galvanised steel 75m UNI EN 1461

COLOUR

- Anthracite RAL 7016 textured
- Metallic grey RAL 9006

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Hole for cable passage (buried part of pole System A)
- Hole on flange for cable passage into pole and hole on pole for earthing cable (System B)
- 3-pole power supply terminal (IP44), and cord-block for Ø15mm max cable included into the pole adapter
- M8 earthing bolt

Rev. 2 - 13/11/19

Details

- IP

