

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Coled TP

**Code : 1062182W**

#### PRODUCT FAMILY

- Outdoor LED luminaire for residential use, to be installed on pole tops Ø60mm, upright mounting (IP65).

#### MATERIALS CHARACTERISTICS

- Top cover in die-cast aluminium (ADC12) anodized and painted with thermosetting powder coating
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Diffuser in traslucent PMMA (acrylic) with brushed effect, sealed with pure neutral silicone, anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays
- Reinforced thermoplastic housing in NY-FV30%
- Silicone gaskets
- Fixing springs in harmonic steel AISI 301
- A2 stainless steel screws

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity

- Hardness, Shore A 37
- Tensile strength MPa 2,5
- Elongation at break %680

#### COLOUR

- Rust
- Grey RAL 9006
- Black textured
- Anthraxite RAL 7016

#### WEIGHT

- Luminaire: 0,75kg
- Single package: 0,9kg (182x192x110mm)

#### LIGHTING CHARACTERISTICS

- Mains powered LED's lighting source in fixed position
- Immediately ON at 100% of light flux
- Monochromatic LED's module (76 LED's)
- PCB in FR4 thickness 1,6mm
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- 15W LED's module supply tension 220-240V 50/60Hz
- PG9 plastic cable gland equipped with osmotic valve for air and humidity leakage (reducing the overpressures)
- Connection to the main supply through a H05RN-F 3x0,75mmq pre-wired cable (100cm) out of the luminaire

#### INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops Ø60mm with maximum thickness 3mm
- Fixing by harmonic steel springs
- Ordinary and extraordinary maintenance not necessary
- The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

#### DIMENSIONS

- Ø175x94mm

#### TECHNICAL SPECS 3000K/4000K


- Led's output: 1737lm@tc25°C
- Luminaire output: 1518lm@ta25°C
- Led's efficiency: 118,8lm/W
- Luminaire efficiency: 101,2lm/W

- Led's consumption: 15W
- Luminaire consumption: 15W
- Step MacAdam: 3
- Lifetime Led's: L70/B50>60Kh Tc 105°C
- Warranty: 3 years

Rev. 5 - 16/02/2023

#### Details

- Conformity with EU Directives
- CLASS I
- IK05
- RG0
- CRI>80
- IP 65



220-240V 50/60Hz 15W					
CE		IK 05	RG	CRI ≥ 80	IP65

