

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Edge pole top

Code : 0170184S

PRODUCT FAMILY

- Urban architectural CUT-OFF LED rectangular shaped 125x90mm for pole top use on Ø60mm poles (IP65)

MATERIAL CHARACTERISTICS

- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
- Interlocking decorative side profile in PC (polycarbonate)
- Reinforced thermoplastic and painted front closure cap
- Round pole top in hot-dipped galvanized steel S235JR UNI EN 10219, 75µm thick UNI EN 1461
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

COLOUR

- Anthracite RAL 7016 textured

LIGHTING CHARACTERISTICS

- LED's lighting source in fixed position
- Monochromatic LED module (48 Led's - 38.5W) powered at 700mA
- Street short LED optics in PMMA (acrylic) with high performances
- Non yellowing, transparent PMMA (acrylic) lens
- Immediately ON at 100% of the light flux
- CUT-OFF light fitting conforming to all regional/local laws against light pollution

WIRING CHARACTERISTICS

- LED circuit secured on the aluminium housing/heat-sink
- Led's Seoul smd 3030
- Driver IP67 included (DALI dimmable version available on request)

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on Ø60mm poles
- Pre-wired with H07RN-F 2x1.5mmq cable (1mt) for the connection to the mains
- Ordinary and extraordinary maintenance (not necessary)

DIMENSIONS

- 125x90x500mm

OPTIONAL ACCESSORY (TO BE ORDERED SEPARATELY):

- Cod. CS160037 Surge protection kit
- When purchased the protection kit will be installed inside the luminaire
- Max impulse voltage UOC 10KV
- Voltage protection level L-N <1500V

TECHNICAL SPECS

- LED's type: Seoul smd 3030
- Step MacAdam: 3
- Lifetime LED's: L90/B50 - 54Kh Tc 105°C
- Warranty: 3 years

TECHNICAL SPECS 4000K

- LED's output: 5088lm@tc25°C
- Luminaire output: 4643lm@ta25°C
- LED's efficiency: 149lm/W
- Luminaire efficiency: 121lm/W
- LED's consumption: 34.1W
- Luminaire consumption: 38.7W
- Power factor: >0.94


TECHNICAL SPECS 3000K

- LED's output: 4741lm@tc25°C
- Luminaire output: 4326lm@ta25°C
- LED's efficiency: 139lm/W
- Luminaire efficiency: 113lm/W
- LED's consumption: 34.1W
- Luminaire consumption: 38.7W
- Power factor: >0.94

Rev. 2 - 28/09/21

Details

- Conformity with CEE directives
- Conforms to all regional/local laws against light pollution
- Double insulation/class II
- IK08
- RG1
- CRI>80
- CLASS A+
- IP 65



90-295V 50/60Hz 38,5W	
CE	CUT OFF
IK 08	RQ
CRI ≥80	A+
IP65	

