

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Slot 64

Code : 4037181N

PRODUCT FAMILY

-Cylindrical luminaire Ø64 mm (IP65) complete with spike for earth installation.

MATERIAL CHARACTERISTICS

- Anodised and painted aluminium housing.
- Anodised and painted aluminium frame Ø64 mm.
- Extra clear tempered flat glass diffuser.
- Silicone gaskets.
- A2 Stainless steel screws.
- PG9 metal cable gland (included).
- Anodised and painted die-cast aluminium spike.

COLOUR

- Black.

LIGHTING CHARACTERISTICS

- Max. lamp diameter allowed: < di 49 mm.
- Lamp must be with flat diffuser.

WIRING CHARACTERISTICS

- GU10 lamp holder.
- Max. Led lamp power allowed: 5W.
- Max. tension allowed: 250V.
- Connection to the mains via cable H05RN-F 3x1mmq L=300 mm (included).

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire complete with spike for earth installation.
- Ordinary maintenance to be conducted by unscrewing the frame with the diffuser.

DIMENSIONS

- Ø64X125X380 mm.


GENERAL SPECS

- 5-Year warranty.



Rev 01-16/03/2023

Details

- Conformity with EU Directives
- CLASS I
- IK08
- IP 65



5W max GU 10

CE			IP65
----	---	---	------

