

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Dracma 110

Code : 5110181G

PRODUCT FAMILY

-IP67 round uplight Ø110mm pre-set for GU10 led lamp, requiring recessed box for floor mounting.

MATERIAL CHARACTERISTICS

- Housing made of painted die-cast aluminium.
- Stainless steel AISI 304 round ring Ø110 mm, sandblasted.
- Drive over: max. load 2000Kg at 20Km/h.
- Extra-clear flat tempered glass diffuser 8mm thick.
- Reinforced thermoplastic recessed box, black colour.
- Silicone gaskets.
- A2 stainless steel screws.

COLOUR

-Stainless steel.

LIGHTING CHARACTERISTICS

- Led light source mains powered in fixed position (light source not included).
- Immediately ON at 100% of the light flux.
- Lamp connection GU10.
- Max. led lamp dimensions allowed: Ø50xL56mm.

WIRING CHARACTERISTICS

- Luminaire designed for GU10 lamp max 35W, mains powered 250V max.
- N°2 PG9 metal cable glands (in – out), included.
- Connections to the mains to be conducted via cable H05RN-F 3x1mmq.

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Inground uplight for use with recessed box (included).
- Ordinary maintenance to be conducted by loosening the 4 fixing screws of the ring and removing the diffuser.
- Round recessed box Ø105X132.5mm.

DIMENSIONS

- Ø105X132,5


Details

- 5-year warranty.

Rev. 1 - 10/03/2023

Details

- Conformity with EU Directives
- CLASS I
- IK08
- IP 67



35W max GU 10			
CE	⊕	IK 08	IP67